## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Currently Amended) A loudspeaker comprising:
  - a support;
  - a diaphragm mounted on the support; and
- a piezoelectric actuator arranged to provide, on activation, relative movement between two ends of the actuator, wherein each of said ends of the actuator is coupled to the diaphragm to vibrate the diaphragm on activation of the actuator, a portion of the diaphragm coupled to one end of the actuator being fixed relative to the support.
- 2. (Cancelled)
- 3. (Currently Amended) A loudspeaker according to claim 21, wherein the one end of the actuator is coupled to a portion of the diaphragm at the edge of the diaphragm.
- 4. (Currently Amended) A loudspeaker according to claim 2 or 31, wherein the diaphragm has an aperture separating portions of the diaphragm coupled to the respective ends of the actuator.
- 5. (Currently Amended) A loudspeaker according to any one of claims 2 to 4claim 1, further comprising a seal member between the diaphragm and the support extending around the periphery of a portion of the diaphragm, wherein the one end of the actuator

is coupled to a portion of the diaphragm outside the seal member and the opposite end of the actuator is coupled to a portion of the diaphragm adjacent or inside the seal member.

- 6. (Currently Amended) A loudspeaker according to any one of claims 2 to 5 claim 1, wherein the actuator is longer in transverse extent than in extent between the two ends.
- 7. (Currently Amended) A loudspeaker according to any one of claims 2 to 6 claim 1, further comprising at least one stop member coupled to the diaphragm adjacent said one end of the actuator and extending to a position adjacent said opposite end of the actuator for limiting the movement of the portion of the diaphragm coupled to the opposite end of the actuator.
- 8. (Currently Amended) A loudspeaker according to any one of claims 2 to 7 claim 1, wherein the portion of the diaphragm coupled to one end of the actuator is fixed relative to the support by being coupled directly to the support.
- 9. (Currently Amended) A loudspeaker according to any one of claims 2 to 7 claim 1, further comprising a rigid bridge element coupled to the one end of the actuator and also coupled to a further portion of the diaphragm separated from the actuator, the portion of the diaphragm coupled to one end of the actuator being fixed relative to the support by the further portion of the diaphragm being coupled to the support.

- 10. (Currently Amended) A loudspeaker according to any one of the preceding claims laim. (Currently Amended) A loudspeaker according to any one of the preceding claims laim.
- 11. (Original) A loudspeaker according to claim 10, wherein said curve is a sector of a circle.
- 12. (Currently Amended) A loudspeaker according to claim 10-or-11, wherein the opposite end of the actuator has an end surface facing the diaphragm.
- 13. (Original) A loudspeaker according to claim 12, wherein said opposite end of the actuator is coupled indirectly to the diaphragm by a spacer.
- 14. (Currently Amended) A loudspeaker according to any one of claims 10 to 13 claim

  10, wherein one end of the actuator is coupled directly to the diaphragm by a side surface of the actuator, the actuator extending from said one end in a loop over said one end.
- 15. (Currently Amended) A loudspeaker according to any one of claims 1 to 9claim 1, wherein the actuator is straight.
- 16. (Currently Amended) A loudspeaker according to any one of the preceding claims claim 1, wherein the actuator has a bender construction.

- 17. (Currently Amended) A loudspeaker according to any one of the preceding claims of the preceding to any one of the preceding claims of the preceding claims of the preceding claims of the preceding to any one of the preceding claims of the prec
- 18. (Currently Amended) A loudspeaker according to any one of the preceding claimsclaim 1, wherein the support is a portion of a housing of an electronic device.
- (Currently Amended) A loudspeaker assembly comprising:
   a diaphragm; and

a piezoelectric actuator arranged to provide, on activation, relative movement between two ends of the actuator, each of said ends being coupled to the diaphragm to vibrate the diaphragm on activation of the actuator, one end of the actuator is coupled to a portion of the diaphragm at the edge of the diaphragm.

- 20. (Cancelled)
- 21. (Currently Amended) A loudspeaker <u>assembly</u> according to claim 19-or 20, wherein the diaphragm has an aperture separating portions of the diaphragm coupled to the respective ends of the actuator.
- 22. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to 21claim 19, further comprising a seal member between the diaphragm and the support extending around the periphery of a portion of the diaphragm, wherein the one end of the actuator is coupled to a portion of the diaphragm outside the seal member

and the opposite end of the actuator is coupled to a portion of the diaphragm adjacent or inside the seal member.

- 23. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to <u>22claim 19</u>, wherein the actuator is longer in transverse extent than in extent between the two ends.
- 24. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to 23claim 19, further comprising at least one stop member coupled to the diaphragm adjacent said one end of the actuator and extending to a position adjacent said opposite end of the actuator for limiting the movement of the portion of the diaphragm coupled to the opposite end of the actuator.
- 25. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to 24claim 19, further comprising a rigid bridge element coupled to the one end of the actuator and also coupled to a further portion of the diaphragm separated from the actuator.
- 26. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to 25claim 19, wherein the actuator extends between the two ends in a curve.
- 27. (Currently Amended) A loudspeaker <u>assembly</u> according to claim 26, wherein said curve is a sector of a circle.

- 28. (Currently Amended) A loudspeaker <u>assembly</u> according to claim 26 or 27, wherein the opposite end of the actuator has an end surface facing the diaphragm.
- 29. (Original) A loudspeaker <u>assembly</u> according to claim 28, wherein said opposite end of the actuator is coupled indirectly to the diaphragm by a spacer.
- 30. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to 29claim 19, wherein one end of the actuator is coupled directly to the diaphragm by a side surface of the actuator, the actuator extending from said one end in a loop over said one end.
- 31. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to 30claim 19, wherein the actuator is straight.
- 32. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to 31claim 19, wherein the actuator has a bender construction.
- 33. (Currently Amended) A loudspeaker <u>assembly</u> according to <del>any one of claims 19</del> to 32claim 19, wherein the actuator comprises ceramic piezoelectric material.